

TECHNICAL DATA SHEET

DELTA®-TILAXX

DESCRIPTION

Solvent-free construction adhesive and sealant. Permanently elastic sealing compound suitable for use with DELTA® membranes. Also adheres to other common building elements.

FEATURES

- Solvent-free
- Quick-setting (depends on temperature and humidity)
- Aggressive tack provides increased adhesion.
- Adheres to:
 - Glass
 - Aluminum
 - Zinc
 - Steel
 - Paints and primers
 - Wood composites
 - Wood
 - Plastics
 - Clay roof tile

USES

DELTA®-TILAXX contributes to the air and water tightness of the building enclosure by sealing overlaps (end laps and side laps) of DELTA® air and water-resistive barriers. DELTA®-TILAXX forms an exceptional bond to common construction materials, making it an ideal component to create continuity in air and water-tight wall and roof assemblies. DELTA®-TILAXX is part of DELTA® premium system accessories that complete a WRB / Air Barrier installation. Designed for applications above 5°C (40°F).

LIMITATIONS

Apply under dry conditions above 5°C (40°F).
 Store DELTA®-TILAXX above 0°C (32°F).
 Do not freeze. Do not use if frozen.

PREPARATION

Surfaces must be dry and free from dust, dirt, grease, oil, ice or other foreign matter.

CAUTION

Harmful if swallowed.
 Do not freeze.

Technical Data

Product name	DELTA®-TILAXX
Color	Black
Material	Solvent-free construction adhesive and sealant
Packaging	12 cartridges / box
Cartridge size	310 ml
Coverage	approx. 7m/cartridge
Shelf life	12 months
Curing time	Skin formation after 25 minutes at 50% humidity
Installation temperature	+ 40 °F to + 90 °F (+ 5 °C to + 30 °C)
Temperature range (in situ)	-40 °F to + 176 °F short term up to 248 °F (-40 °C to + 80 °C short term up to 120 °C)
Suitable for use with	DELTA®-VENT S, DELTA®-VENT SA, DELTA®-STRATUS SA, DELTA®-FASSADE S & DELTA®-FASSADE SA



DELTA® products support sustainable and energy-efficient building practices, including efforts toward achieving LEED® certification (LEED® for New Construction & Major Renovations, LEED® for Core and Shell, LEED® for Existing Buildings and LEED® for Homes).

For technical support, call our technical support team at 1-888-4DELTA4 (1-888-433-5824) extension 326, or visit www.dorken.com.